(12) AUSTRALIAH PATENT ABRIDGMENT (19) AU

(11) AU-B-75789/81

	•						
(54)	GAMINS APPARATUS						
(71)	BALLY MANUFACTURING CORPORATION						
(21)	75789/81	543997	(22) 30.9.81				
		•	(24) 30.9.80				
(31)	8031544	(32) 30.9.80	(33) GB.				
(43)	8.4.82		(44) 16.5.85				
· (.51).3.	GO7F 17/34	•					
(72)	BARRINGTON KEITH THOMPSON						
(74)	SF						
(56)	44475/79 524709 39332/78	GO7F 17/34 GO7F 17/34					
(57)	Claim ·						

Gaming apparatus having a known ordered series of indicia defined by the apparatus; indicia display means to display to a player of the gaming apparatus a selected one of the known ordered series of indicia; gamble control means operable by the player to select a class of indicia defined by either all the indicia of higher order or all the indicia of lower order in the known ordered series relative to the displayed selected one of the known ordered series: random selection means to select a new indicium of the known ordered series of indicia following said player's use of said gamble control means, compare means to determine if the randomly selected new indicium of the known ordered series of indicia is in the class of indicia selected by the player; and win means to produce a predetermined win response if the randomly selected new indicium of a known ordered series of indicia is in the class of indicia selected by the player.

16

0

PATENTS ACT 1952

COMPLETE SPECIFICATION

(ORIGINAL)

FOR OFFICE USE :.

Class

Int. Class

Application Number: 75789/87

Complete Specification Lodged:

Accepted : Published :

Priority .

, ; सैश्रीदारत Art :

Finis ducument tantishes the emediatem to section to made mediatem to correct for printing.

Nume of Applicant :

BALLY MANUFACTURING CORPORATION

Address of Applicant :

2640 West Belmont Avenue, Chicago, Illinois, United States of America

BARRINGTON KEITH THOMPSON

Address for Service :

Actual inventor :

Spruson & Ferguson, Patent Attorneys, CBA Centre 50 Margaret Street, Sydney, New South Wales, 2000 Australia

Complete Specification for the invention entitled :

"GAMING APPA, "TUE"

The following statement is a full description of this invention, including the bast method of performing it known to need as

GAMING APPARATUS

The present invention concerns gaming apparatus. The invention is a especially, though not exclusively, con-5 cerned with an improvement to so-called fruit machines. Fruit machines, also known as slot machines, are well known. Rowever, for the avoidance of doubt, a fruit machine is hereby defined for the purpose of this specification as an apparatus which in response to a playing stake from a play-10 er automatically selects at random and displays a group of two or more indicia from a predetermined collection of indicia and provides a win response of the selected and displayed group of indicia corresponds to a predetermined winning combination of the indicia. The win response is 15 usually a predetermined value credit to the player and there may be a number of different winning combinations providing wins of different value. It is also known and common for a win response to provide a player with the option of operating various so-called play features to gamble on or improve the basic win. In most fruit machines, the indicia are provided as markings around the outer edges of three or more rotatable reels, typically having a common axis of rotation. The reels are rotated and stopped at randomly selected angular positions. At the periphery of 25 each reel is a window exposing at least one indicium of each reel, and the exposed indicia when the reels stop constitute the selected group which may or may not be a winning combination. The windows are usually in a line parallel to the common axis of the reels and they may ex-30 pose up to three adjacent indicia on each real with a socalled win line defined at the windows identifying the group of indicia which may be a winning combination. A number of so-called play features are well known. For example, there is the HOLD feature whereby one

35 or more of the reels may be prevented from rotating, to



GAMING APPARATUS

ABSTRACT

A gaming machine has a display 28 of an ordered series of indicia, e.g. numbers or playing cards. A

5 player can press a chosen gamble button 30, 31 to select either the indicia values of higher or of lower order than the displayed. The machine then selects a new indicium at random, e.g. by microprocessor 19 and displays the new selected indicium. If this tallies with the player's gamble selection a win is awarded. The machine can be provided as a feature play of a fruit machine with the gamble selection done on an extra fruit machine reel 16.

hold the previously selected indicia, during a subsequent playing cyclecot the machine. In another example, following a win, the player, is offered the chance of gambling the win, double or quits. Another popular feature is the so-called Nudge feature described in Birtish Patent No. 1292712.

The gaming apparatus of the present invention can conveniently believed as a play feature in a fruit machine. However withe gaming apparatus may also form a separate game libdependent of a fruit machine, or may form part of a different game.

ered series of indiciaay means to display to a paparatus a selected one of the known lercontrol means operable by the polayer conselect a classion indicia defined by either all the indicia of higher order or all the indicia of lower order in the Enoun ordered series relative to the displayed selected one of the known ordered series; random selection means to select a new indictum of the known of dered series of indicia following said blayer's use of said gamble control means; compare means to determine if the randomly selected new indicium of the known crdered series of indicia is in the class of indicia selected by the player; and win means to produce a predetermined win response if the randomly selected new indicium of a known ordered series of indicia is in the class of indicia selected by the player. The ordered series of indicia in the above apparatus may comprise any series of indicia which fall in a generally known ordered series. For example, the indicia may be letters of the alphabet where A is the beginning of the series and Z is

-2-

DJC/126H

BALLY003078

75769/81

Best Available Copy

the end of the series. Alternatively, the indicia may be a series of numbers, or they may be values of playing cards. The gaming apparatus operates by permitting the player to guess whether the indicum to be selected at random will be of higher value of lower value in the ordered series than the indicum on displayed it the prayer guesses correctly, then the apparatus provides always response. It is normally desirable that means



75789/31

the fresh randomly selected indicium after said camble selec-

The display means may be arranged to display the freeh fancomic selected indicion as said selected one of the undednation to a burther camble selection by the player. Then sollowing an initial samble by the player and random selection by the random selection by the random selection by the random selection by the random selection to the random selection to the random selection to the random selection.

standard value credit to the player. However, any other win response that walks be employed which provides an attraction to the credits.

The who media may elso produce a predetermined loss respected in the tree track details and indicion is one of the indicion mot selected by the player, i.e. if the player guesses wrongly. The Pose response may be a standard value debit to the player.

Notingly, the apparatus includes an initiate control operable by the player to initiate operation of said random selection means. Nowever, the apparatus may electroatively respond automatically to estuation by the player of said gamble selection means to initiate operation of said random selection means.

In one example, the random selection means includes a window in the apparatus, a rotatable real behind the window having the indicis marked about an annular or circumferential surface of the real whereby one of the indicis markings on the real can be viewed through the window as the selected indicium depending on the angular position of the real, means to rotate the real and means to stop rotation of the real at a randomly

Service Should position to make said random selection of the linguistic running even that slich a preferred embodiment lends itself to incorporation in the composition of the useal kind.

-4-

Accordingly, the present invention also envisages a fruit mechine as hereinbefore defined incorporating the above-described gaming apparatus and having means activating the gaming apparatus to make the apparatus available for play by the player of the fruit machine as a play feature following a normal play sequence of the fruit machine. Convendently, said activating means is arranged to activate the apparatus only following a winning play sequence of the fruit machine. Then, if the player obtains a winning combination on the fruit machine in a normal play sequence, the player may be offered the chance of operating the gaming apparatus to increase the value of his win.

Typically, said activating means is arranged to activate the apparatus at random in response to a proportion of wheming play sequences of the fruit machine. The activating means may maintain the apparatus activated for repeated further sample selections by the player until the fresh randomly selected indicium is one of the indicio not selected by the player. In this way, the player can repeatedly increment his win until he makes a wrong guess.

An example of the present invention is now described with reference to the enclosed drawing which shows schematically a fruit machine incorporating gening appuratus tus embodying the present invention.

A typical fruit machine or slot machine has a real essembly containing the usual rotatable reals of the machine having the fruit symbols or indicis market on the outer adges of the reals. The real assembly usually comprises the mounting arrangements for the reals, the drive arrangement to rotate the reals together with arrangements to stop the reals as desired and usually subject to control signals from control apparatus in the machine. The real assembly also usually contains detector means for detector the angular positions of the reals so that at least the

possitions of the reals efter they are scopped can be desetting that escribe can be known to determine whether they of the finit escribe can be known to determine whether they before winning combination. In some excempenents the reals specification of an electric motor, for example, a stupping sorting the stopped and started by stopping and starting the motor expendentally. In other arrangements, the reads size soin and stopped by solenoid and retchet arrangeousn's.

En the expanse of the present invention illustration in the figure, a real assembly for a fruit machine as included consensity at 10. The details of the real escability in the internal in the figure. The real assembly may compare established any of the known types of real assembly displaying in the finit exchine are.

The head especially li has four rotatable reals li to 14. Apply 41 to 13 constitute the usual freit machine reems bendity the usual fruit symbols marked on their outer 20 edges es et 15. The faurth seel 14 constitutes e feeture seed of the front machine enebling a play feature to be playes on the machine is accordance with this embodiment of the invention. The real la has indicis marked about its outer edge as at ME. The indicia it are all members of an 25 oxdexed series of irdicia such that a player of the machine can immadiately recognise whather one indicium of the series is of a higher or lower order than another indicium in the series. In the illustrated example, the incidia are simply numbers. It is not essential for the numbers 30 16 to be arranged about the reel 14 in numerical order. nor is it essential that each number is different from every other number on the real 14. It is only necessary that there are several different numbers located about the perichery of the reel 14. It is however preferable that 35 the numbers 16 on the real form a continuous series with10

out any gaps, for example, all the numbers from 1 to 13, and also that each number appears on the soci li an equal number of times. This ensures that with random scopping 5 of the reel 14, the number 16 appearing behind the win line of the machine as will be emplained later is randomly selected from the series.

Instead of numbers 16 the indicis on the real 14 could be letters of the alphabet or playing card values.

The reel assembly 10 is located in the fruit machine behind a window 17 in a front panel of the machine so that, in the usual way, at least one indicium of each of the reels can be seen through the window when the reels stop. Commonly, the wirdow 17 is made sufficiently big so ib that three or more edjacent indicia from each real can be viewed through the window, in which case a win line 18 is marked on or adjacent the window to identify the indicia on the stopped reels which are to be considered for a winsing combination. In the present example, the win line 12 20 also identifies the number 16 on the reel 14 which is rem-Somly selected by operation of the machine as will be exolzined.

The normal game sequence of the fruit machine is the present example can erate in any known way in the 25 art. The overall control of operation of the fruit machine in the illestrated example is maintained by a microprocessor system comprising a Microprocesor ly connected in data communication with a random access memory RAM 20 and a read only memory ROM 21 by means of data buses 22. Data input 30 to the microprocessor system, for example, from switches operated by a player of the machine, is controlled via an ingur/output interface unit 13 also connected to the data bus 22. The interconnection and design of the microprodessor system comprising the minroprocessor 19 FAM 20 NOW 35 21 and interface unit 23 is simply a matter of design

Eully within the capability of the experienced engineer working in this field and forms no part of the present invention. Furthermore, the detailed programming of the 5 microprocessor system is also a matter for the experienced design engineer and programmer. In a typical standard game cycle of a fruit machine, the microprocessor responds to input signals indicating a player has inserted sufficient coins or tokens into the machine to have credit for 10 a game to enable an initiate button. When the player presses the initiate button on the fruit machine, the minroprocessor responds by sending signals via the interface unit 23 to the reel assembly 10 along a line 24 to initiate spinning of at least the reels li to 13 of the 13 machine. The reels 11 to 13 may be stopped by autonomous action of the reel assembly 10 but, more typically, they are stooped also by specific convrol from the microprocessor. Once the reels 11 to 13 are stopped, the angular positions of the stopped reels are determined and data 20 defining the stop positions supplied to the microprocessor via the interface unit 23 along a line 25. The microprocessor 19 then identifies the symbols on the roels 11 to 11 appearing at the win line 18, typically by reference to data in the 20M 21, and further determines whether 25 these symbols constitute a winning combination again by reference to data in the ROM 21. If a win is indicated, the microprocessor provides signals again via the interface unit to operate an appropriate credit or pay-out to

In the present example embodying this invention, following a win combination of the stopped roels !] to !? as determined by the microprocessor 19, the microprocessor 19 then enables a feature play before initiating the payout. This may be indicated to the player of the machine 35 Ev a flashing light 27 on the front panel of the machine operrolled by the airropiocessor via the interface unit 72.

the player by a pay-out unit 26.

34.

At the same time, the microprocessor 19 selects one of the numbers 16 of the reel 14 and displays this number on a display 28 which is controlled by data on a line 29 from 5 the interface unit 23. Then, on inspecting the number displayed by the display 28, the player decides whether to gamble that a future random selection will produce a number from the series on the reel 14 either higher or lower then that displayed on the display 28. The fruit machine ic will normally have clearly visible instructions on its front panel making it clear to the player the range of numbers from which the selection will be made. For example, if the range is from the numbers 1 to 13, and the number displayed on the display 28 is number 9, then the player 15 might consider it most likely that a future random selection would produce a number lower than number 9 from the series. The player would indicate the selection by pressing a button 30 marked LOMER. If on the other hand the player considered it more likely the selection would pro-20 duce a higher number, he would press a buston 31 marked HIGHER. The player's selection is supplied to the microprocessor 19 along lines 32 and 33 via the interface unit 23. Pollowing selection by pressing one of the buttons 30 and 31 the player initiates the automatic random selection 25 by the machine by pressing an IMITIATE button 34 which signals to the microprocessor along a line 35 via the interface unit 23. The microprocessor 19 responds by instructing the reel assembly 10, along the line 24, to spin the real 14 and subsequently stop the real at a randomly 30 selected angular position. The random selection of the machine is then indicated by the number 16 of the reel 14

The position of the real 14 after stopping is supplied to the microprocessor 19 along the lines 25 and the microprocessor 19 determines the number 15 on the win line 18 by comparison with data in POM 21 and compares

appearing behind the win line 18.

this number with the number being displayed on the display 26. If the comparison agrees with the MIGHER/LOWER selection by the player, then the microprocessor 19 provides a win response by instructing the credit/debit pay-out unit 25, vie the interface unit 23 to credit the player with a stendard value.

programmed also to maintain the availability of the play
feature following a winning selection by a player so that
the player can subsequently semble again. Then, the microprocessor 19 automatically changes the number displayed on
the display 28 so as to correspond with the randomly selected number from the real 14 on the win line 18. Thus, the
number in the display 28 is changed automatically following a correct or winning selection by rie player. However,
if the player makes a losing selection, the microprocessor
19 responds by discontinuing the availability of the play
feature. The original value on the display 28 is then
left to enable the player to compare it minually with the
random selection on the real 14.

There are various modifications of the jame forture embodying this invention. It may be ineferred to provide the feature as a "no lose" feature so that when the

25 feature is offered, the player reactions a solution during
following each correct selection, but following a wrong
selection, the feature is simply discontinued and the
player has the option of promoding with a further a real
play sequence of the fruit machine. In this error wheat,
35 it will normally be desirrable to provide a semi-sum master
of repeated feature plays following vaccousive correct
selections by a player to limit the maximum for all equitable on a particular sequence. For exactly, a player may
be able to make correct selections up to a maximum of the
53 successive times after which the material of the processive times after the process

matically discontinues availability of the feature so that the game proceeds to a normal cycle.

In another arrangement, the microprocessor may 5 arrange to provide a debit of a standard value against a player following a wrong selection by the player.

Purthermore, it may be desirable to limit the number of times upon which the feature is made available following a winning combination of the normal fruit machine play cycle. Thus, the play feature embodying the present invention is made available only at random following a proportion of winning combinations.

The example of this invention described with reference to the accompanying drawing includes a microprocessor system. However, it should be apparent that other ways of engineering the present invention are possible and within the ability of the design engineer. For example, the microprocessor system may be replaced by an electro-mechanical or electronic logic system designed specifically for the purpose intended.

In playing the game feature described above, it will be apparent that it is possible the randomly selected number from the real 14 may be equal to the number in the display 26. The way in which the microprocessor 19 is arranged to respond to this situation is for the designer to decide. The microprocessor may treat such an identical selection as either a win or as a lose. In the "no lose" example described above, it may be preferable to programme the microprocessor 19 to respond to an identical selection by discontinuing availability of the feature. However, in other arrangements, the microprocessor may be programmed to respond to an identical selection with a bonus win, perhaps at the same time discontinuing further evailability.

The example of the present invention illustrated in the 35 Grawing, employs a reel associaty 10 with researche reels

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☑ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☒ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
▼ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
□ OTHER:

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

as common in fruit machines. However, other techniques of making a random selection of the indicia of the ordered series may be used. For example, the fruit machine may have a television-type screen on which the normal fruit symbols are displayed subject to the control of electronic circuitry. Then, the random selection may take place purely in the circuitry of the machine with the selected indicium being displayed on the screen.

Furthermore, although in the present example, an embodiment of the invention has been described as a play feature of a normal fruit machine, it will be appreciated that other embodiments of the present invention are possible quite independent from fruit machines. The principles of the game apparatus of the present invention can be embodied separately in appropriate apparatus or as additional features in different game machines.

10

The claims defining the invention are as follows:

- Gaming apparatus having a known ordered series of indicia defined by the apparatus; indicia display means to display to a player of the gaming apparatus a selected one of the known ordered series of indicia; gamble control means operable by the player to select a class of indicia defined by either all the indicia of higher order or all the indicia of lower order in the known ordered series relative to the displayed selected one of the known ordered series; random selection means to select a new indicium of the known ordered series of indicia following said player's use of said gamble control means; compare means to determine if the randomly selected new indicium of the known ordered series of indicia is in the class of indicia selected by the player; and win means to produce a predetermined win response if the randomly selected new indicium of a known ordered series of indicia is in the class of indicia selected by the player.
 - Gaming apparatus as claimed in claim 1 wherein means are provided to display the fresh randomly selected indicium.
 after said gamble selection.
 - 3. Gaming apparatus as claimed in claim 1 or claim 2 wherein said display means is arranged to display the fresh randomly selected indicium as said selected one of the indicia for a further gamble selection by the player.
 - 4. Gaming apparatus as claimed in any preceding claim wherein said win response is a standard value credit to the player.
- 5. Gaming apparatus as claimed in any preceding claim wherein said win means produces a predetermined lose response if the fresh randomly selected indicium is one of the indicia not mJC/126M —12- 75789/81

selected by the player.

- 6.. Gaming appearatus as claimed in claim 5 wherein said lose response is a standard value debit to the player.
 - 7. Gaming apparatus as claimed in any preceding claim and including an intiate control operable by the




player to initiate operation of said random selection means.

- 8. Gaming apparatus as claimed in any preceding claim wherein said random selection means includes a window in the apparatus, a rotatable reel behind the window having the indicia marked about an annular or circumferential surface of the reel whereby one of the indicia markings on the reel can be viewed through the window as the selected indicium depending on the angular position of the reel, means to stop rotation of the reel at a randomly selected angular position to make hald random selection of the indicium viewed through the window.
- 9. A fruit machine, as hereinbefore defined incorporating a gaming apparatus as claimed in any preceding claim and having means activating the gaming apparatus to make the apparatus available for play by the player of the fruit machine as a play feature following a normal play seguence of the fruit machine.
 - 10. A fruit machine as claimed in claim 9 wherein said activating means activates the apparatus only . following a winning play sequence of the fruit machine.

20

- 11. A fruit machine as claimed in claim 10 wherein said activating means is arranged to activate the apparatus at random in response to a proportion of winning play sequences of the fruit machine.
- 12. A fruit machine as claimed in any of claims 5 to 11, as dependent from claim 3, wherein said activating means maintains the apparatus activated for repeated further gamble selections by the player until the fresh randomly selected indicium is one of the incidia not selected by the player.
- 13. A fruit machine substantially as hereinbefore fuscribed with reference to and as illustrated in any 35 of the accompanying drawings.



(12) AUSTRALIAN PATENT ABRIDGMENT

(11) AU-B-75789/81

						•	
(54)	GAMING APPARATUS						
(71)	BALLY MANUFACTURING CORPORATION						
(21)	75789/81	•	5439	97	(22)	30.9.81	
					(24)	30.9.80	
(31)	8031544		(32)	30.9180	(33)	GB	
(43)	8.4.82	•			(44)	16.5.85	
(.51).3	G07F 17/34						
(72)	BARRINGTON KEITH THOMPSON						
(74)	SF						
. (56)	44475/79 39332/78	524709		17/34 17/34			
(57)	Claim	•					

Gaming apparatus having a known ordered series of indicia defined by the apparatus; indicia display means to display to a player of the gaming apparatus a selected one of the known ordered series of indicia; gamble control means operable by the player to select a class of indicia defined by either all the indicia of higher order or all the indicia of lower order in the known ordered series relative to the displayed selected one of the known ordered series: random selection means to select a new indicium of the known ordered series of indicia following said player's use of said gamble control means, compare means to determine if the randomly selected new indicium of the known ordered series of indicia is in the class of indicia selected by the player; and win means to produce a predetermined win response if the randomly selected new indicium of a known ordered series of indicia is in the class of indicia selected by the player.

16 i

PATENTS ACT 1952

COMPLETE SPECIFICATION

(ORIGINAL)

FOR OFFICE USE ::

Class

Int. Class

Application Number :

75789/81

Lodged:

Complete Specification Lodged:

· Accepted :

Published:

Priority :

Related Art :

Finis document contains the emeadments made needer correct for printing.

Nume of Applicant :

BALLY MANUFACTURING CORPORATION

Address of Applicant:

2640 West Belmont Avenue, Chicago, Illinois,

United States of America

Actual inventor :

BARRINGTON KEITH THOMPSON

Address for Service :

1

Spruson & Ferguson, Patent Attorneys, CBA Centre 60 Margaret Street, Sydney, New South Wales, 2000 Australia

Complete Specification for the invention entitled :

"GAMING APPA, " TUE"

GAMING APPARATUS

The present invention concerns gaming apparatus. The invention is a especially, though not exclusively, con-5 cerned with an improvement to so-called fruit machines. Fruit machines, also known as slot machines, are well known. However, for the avoidance of doubt, a fruit machine is hemeby defined for the purpose of this specification as an apparatus which in response to a playing stake from a play-10 er automatically selects at random and displays a group of two or more indicia from a predetermined collection of indicia and provides a win response of the selected and displayed group of indicia corresponds to a predetermined winning combination of the indicia. The win response is 15 usually a predetermined value credit to the player and there may be a number of different winning combinations providing wins of different value. It is also known and common for a win response to provide a player with the option of operating various so-called play features to gamble 20 on or improve the basic win. In most fruit machines, the indicia are provided as markings around the outer edges of three or more rotatable reels, typically having a common axis of rotation. The reels are rotated and stopped at randomly selected angular positions. At the periphery of 25 each reel is a window exposing at least one indicium of each reel, and the exposed indicia when the reels stop constitute the selected group which may or may not be a winning combination. The windows are usually in a line parallel to the common axis of the reels and they may ex-30 pose up to three adjacent indicia on each real with a socalled win line defined at the windows identifying the group of indicia which may be a winning combination.

A number of so-called play features are well known. For example, there is the HOLD feature whereby one or more of the reels may be prevented from rotating, to

GAMING APPARATUS

ABSTRACT

A gaming machine has a display 28 of an ordered series of indicia, e.g. numbers or playing cards. A player can press a chosen gamble button 30, 31 to select either the indicia values of higher or of lower order than the displayed. The machine then selects a new indicium at random, e.g. by microprocessor 19 and displays the new selected indicium. If this tallies with the player's 10 gamble selection a win is awarded. The machine can be provided as a feature play of a fruit machine with the gamble selection done on an extra fruit machine reel 16.

mold the previously selected indicia, during a subsequent playing cyclerof, the machine. In another example, following a win, the player is offered the chance of gambling the win, double of guits. Another popular feature is the so-called Nudge feature described in British Patent No. 1292/12.

The gaming apparatus of the present invention can conveniently be used as a play feature in a fruit machine. However the gaming apparatus may also form a separate game independent of a fruit machine, or may form part of a different game.

ent invention, there is provided ng apparatus havang a chown ordered series of indicia defined by the apparatus play means to display to a er of the gaming apparatus a selected one of the known ordered series of indicial gamble control means operable by the player to select a class of indicia defined by either all the indicia of higher order or all the indicia of lower order in the known ordered series relative to the displayed selected one of the known ordered series random selection means to select a new indicium of the known ofdered series of indicia following said player's use of said gamble control means; compare means to determine if the randomly selected new indicium of the known ordered series of indicia is in the class of indicia selected by the player; and win means to produce a predetermined win response if the randomly selected new indicium of a known ordered series of indicia is in the class of indicia selected by the player. The ordered series of indicia in the above apparatus may comprise any series of indicia which fall in a generally known ordered series. For example, the indicia may be letters of the alphabet where A is the beginning of the series and Z is

Spac/15em

,0+e^

the end of the series. Alternatively, the indicia may be a series of numbers, or they may be values of playing cards. The gaming apparatus operates by permitting the player to guess whether the indicium to be selected at random will be of higher value or lower value in the ordered series than the indicum on display. If the player guesses correctly, then the apparatus provides a win response. It is normally desirable that means are provided to display



Ene fresh mandomly selected indicium after said gamble selec-

The display means may be arranged to display the tresh randomly selected indicium as said selected one of the undicina for a further gamble selection by the player. Then to live in this all camble by the player and random selection by the dapperature, the player may be offered a further chance to camble starting from the Treshly selected indicion.

standard while credit to the phaser. However, any other win response many also be employed which provides an attraction to the phaser.

The win majors may also produce a predetermined loss response to the tracks may be a standard value debit to the player.

Mormakit, the apparatus includes an initiate control operable by the player to initiate operation of said random selection means. However, the apparatus may alternatively respond automatically to actuation by the player of said gamble selection means to initiate operation of said random selection means.

In one example, the random selection means includes a window in the apparatus, a rotatable real behind the window having the indicis marked about an annular or circumferential surface of the real whereby one of the indicis markings on the real can be viewed through the window as the selected indicium depending on the angular position of the real, means to rotate the real and means to stop rotation of the real at a randomly

30

Selected angular position to make said random selection of the production viewed through the window. It can be seen that such a preferred embodiment lends itself to incorporation in a light machine of the usual kind.

Accordingly, the present invention also envisages a fruit machine as becambefore defined incorporating the about-described gaming apparatus and having means activating the gaming apparatus to make the apparatus available for play by the player of the fruit machine as a play feature following a normal play sequence of the fruit machine. Conveniently, said activating means is arranged to activate the apparatus only following a winning play sequence of the fruit machine. Then, if the player obtains a winning combination on the fruit machine in a normal play sequence, the player may be offered the chance of operating the gaming apparatus to increase the value of his win.

Typically, said activating means is arranged to setivate the apparatus at random in response to a proportion of winning play sequences of the fruit mechine. The activating means may maintain the apparatus activated for repeated further gamble selections by the player until the fresh randomly selected indicium is one of the indicia not selected by the player. In this way, the player can repeatedly increment his win until he makes a wrong quess.

An example of the present invention is now described with reference to the enclosed drawing which shows schematically a fruit machine incorporating gaming apparatus embodying the present invention.

A typical fruit machine or slot machine has a reel assembly containing the usual rotatable reals of the machine having the fruit symbols or indicis marken on the outer edges of the reels. The real assembly usually comprises the mounting arrangements for the reals, the drive arrangement to rotate the reels together with arrangements to stop the reals as desired and usually subject to control signals from control apparatus in the machine. The real assembly also usually contains detector means for detecting the angular positions of the reals so that at least the

positions of the remis efter they are scopped can be detedfestor determines, so that the symbols on the win line of the fruit machine can be known to determine whether they 5 ame winning combination. In some arrangements the reels are gotales by an electric motor, for exemple, a stepping Hotips and and stopped and started by alopping and starting the adios appropriately. In other arrangements, the reels, she span and stopped by soluncid and retoket arrange-තපසුදුළු.

In the exemple of the present invention illustransplay the fingular a real assembly for a fruit machine is iddicated experdity at 10. The details of the real essently 10 are not shown in the figure. The reel assembly THE CHARGE ESSENTIALLY MAY OF the known types of reel assisting discosy legiployed in the India machine art.

30

25

Trè les assembly lo has four votatable reels li to 14. Weeks Al to 13 constitute the usual fruit machine reeds banding the winel fract symbols marked on their outer edges es es la. The Equity usel 14 constitutes a feature reel of the Sanit machine enchling a play feature to be playes on the hackine is accordance with this embodiment of the inmebbion. The real 14 has indicis marked about its outer edge as at 16. The indicis is are all members of an ordesed series of irdicia such that a player of the machine can immediately recognise whether one indicium of the sories is of a higher or lower order than another indicium in the series. In the illustrated example, the incidia are simply numbers. It is not essential for the numbers 30 16 to be arranged about the reel 14 in numerical order. nor is it essential that each number is different from every other number on the real 14. It is only necessary that there are several different numbers located about the periphery of the reel 14. It is however preferable that the sembers 16 on the reci form a continuous series with-

out any gaps, for example, all the numbers from 1 to 13, and also that each number appears on the rec; ld an equal number of times. This ensures that with random scopping 5 $\,\mathrm{e}^{-}$ the reel 14, the number 16 appearing behind the wim line of the machine as will be explained later is randomly selected From the series.

Instead of numbers 16 the indicis on the reel 14 could be letters of the alphabet or playing card values.

10

The reel assembly 10 is located in the fruit machine behind a window 17 in a front penel of the machine so that, in the usual way, at least one indicium of each of the reels can be seen through the window when the reels stop. Commonly, the wirdow 17 is made sufficiently big so 15 that three or more adjacent indicia from each reel can be viewed through the window, in which case a win line 18 is marked on or adjacent the window to identify the indicia on the stopped reels which are to be considered for a winming combination. In the present example, the win line 18 20 also identifies the number 16 on the reel 14 which is randomly selected by operation of the machine as will be exalained.

The normal game sequence of the fruit machine in the present example can wrate in any known way in the 25 ert. The overall control of operation of the fruit machine in the illustrated example is maintained by a microprocessor system comprising a microprocesor 19 connected in data communication with a random access memory RAM 20 and a read only memory ROM 21 by means of data buses 22. Data input 30 to the microprocessor system, for example, from switches operated by a player of the machine, is controlled via an input/output interface unit 23 also connected to the data bus 22. The interconnection and design of the microprocessor system comprising the microprocessor 19 PAM 20 ROM 35 21 and interface unit 23 is simply a matter of design

fully within the capability of the experienced engineer working in this field and forms no part of the present invention. Furthermore, the detailed programming of the

- 5 microprocessor system is also a matter for the experienced design engineer and programmer. In a typical standard game cycle of a fruit machine, the microprocessor responds to input signals indicating a player has inserted sufficient coins or tokens into the machine to have credit for
- 10 a game to enable an initiate button. When the player presses the initiate button on the fruit machine, the microprocessor responds by sending signals via the interface unit 23 to the reel assembly 10 along a line 24 to initiate spinning of at least the reels 11 to 13 of the
- 15 machine. The reels 11 to 13 may be stopped by autonomous action of the reel assembly 10 but, more typically, they are stopped also by specific control from the microprocessor. Once the reels 11 to 13 are stopped, the angular positions of the stopped reels are determined and data
- defining the stop positions supplied to the microprocessor vie the interface unit 23 along a line 25. The microprocessor 19 then identifies the symbols on the reels 11 to 13 appearing at the win line 18, typically by reference to date in the ROM 21, and further determines whether
- these symbols constitute a winning combination again by reference to data in the ROM 21. If a win is indicated, the microprocessor provides signals again via the interface unit to operate an appropriate credit or pay-out to the player by a pay-out unit 26.
- In the present example embodying this invention, following a win combination of the stopped reels II to I3 as determined by the microprocessor 19, the microprocessor 19 then enables a feature play before initiating the payout. This may be indicated to the player of the pachine
- 35 by a flashing light 27 on the front panel of the machine controlled by the micropicewssor via the interface unit 22.

At the same time, the microprocessor 19 selects one of the numbers 16 of the reel 14 and displays this number on a display 28 which is controlled by data on a line 29 from 5 the interface unit 23. Then, on inspecting the number displayed by the display 28, the player decides whether to gamble that a future random selection will produce a number from the series on the reel 14 either higher or lower than that displayed on the display 28. The fruit machine 16 will normally have clearly visible instructions on its front panel making it clear to the player the range of numbers from which the selection will be made. For example, if the range is from the numbers 1 to 13, and the number displayed on the display 28 is number 9, then the player 15 might consider it most likely that a future random selection would produce a number lower than number 9 from the series. The player would indicate the selection by pressing a button 30 marked LOWER. If on the other hand the player considered it more likely the selection would produce a higher number, he would press a button 31 marked HIGHER. The player's selection is supplied to the microprocessor 19 along lines 32 and 33 via the interface unit 23. Following selection by pressing one of the buttons 30 and 31 the player initiates the automatic random selection 25 by the machine by pressing an INITIATE button 34 which signals to the microprocessor along a line 35 via the interface unit 23. The microprocessor 19 responds by instructing the reel assembly 10, along the line 24, to spin the reel 14 and subsequently stop the reel at a randomly selected angular position. The random selection of the machine is then indicated by the number 16 of the reel 14

The position of the reel 14 after stopping is supplied to the microprocessor 19 along the lines 25 and 35 the microprocessor 19 determines the number 16 on the win line 16 by comparison with data in POM 21 and compares

appearing behind the win line 12.

this number with the number being displayed on the display 26. If the comparison agrees with the HIGHER/LOWER selection by the player, then the microprocessor 19 provides a win response by instructing the credit/debit pay-out unit 25, via the interface unit 23 to credit the player with a standard value.

In the present example, the microprocessor 19 is programmed also to maintain the availability of the play feature following a winning selection by a player so that the player can subsequently gamble again. Then, the microprocessor 19 automatically changes the number displayed on the display 28 so as to correspond with the randomly selected number from the reel 14 on the win line 18. Thus, the number in the display 28 is changed automatically following a correct or winning selection by the player. However, if the player makes a losing selection, the microprocessor 19 responds by discontinuing the availability of the play feature. The original value on the display 28 is then left to enable the player to compare it visually with the random selection on the reel 14.

There are various modifications of the jame forture embodying this invention. It may be ireferred to provide the feature as a "no lose" feature so that when the
25 feature is offered, the player receives a serious dicredit
following each correct selection, but following a wrong
selection, the feature is simply discretioned and the
player has the option of promoding with a faction of the
play sequence of the fruit rachine. In this error went,
30 it will normally be desirable to provide a santisum mader
of repeated feature plays following successive correct
selections by a player to limit the rescent result and the
able on a particular sequence. For exactle, a player may
be able to make correct selections up to a maximum of ten
53 successive times after which the retaining of the

matically discontinues availability of the feature so that the game proceeds to a normal cycle.

In another arrangement, the microprocessor may arrange to provide a debit of a standard value against a player following a wrong selection by the player.

Furthermore, it may be desirable to limit the number of times upon which the feature is made available following a winning combination of the normal fruit machine play cycle. Thus, the play feature embodying the present invention is made available only at random following a proportion of winning combinations.

The example of this invention described with reference to the accompanying drawing includes a microprocessor system. However, it should be apparent that other ways of engineering the present invention are possible and within the ability of the design engineer. For example, the microprocessor system may be replaced by an electro-mechanical or electronic logic system designed specifically for the purpose intended.

15

20

In playing the game feature described above, it will be apparent that it is possible the randomly selected number from the real 14 may be equal to the number in the display 28. The way in which the microprocessor 19 is arranged to respond to this situation is for the designer to decide. The microprocessor may treat such an identical selection as either a win or as a lose. In the "no lose" example described above, it may be preferable to programme the microprocessor 19 to respond to an identical selection by discontinuing availability of the feature. However, in other arrangements, the microprocessor may be programmed to respond to an identical selection with a bonus win, perhaps at the same time discontinuing further availability.

The example of the present invention illustrated in the 35 drawing, employs a real assembly 10 with retarable reals

as common in fruit machines. However, other techniques of making a random selection of the indicia of the ordered series may be used. For example, the fruit machine may have a television-type screen on which the normal fruit symbols are displayed subject to the control of electronic circuitry. Then, the random selection may take place purely in the circuitry of the machine with the selected indicium being displayed on the screen.

Furthermore, although in the present example, an embodiment of the invention has been described as a play feature of a normal fruit machine, it will be appreciated that other embodiments of the present invention are possible quite independent from fruit machines. The principles of the game apparatus of the present invention can be embodied separately in appropriate apparatus or as additional features in different game machines.

The claims defining the invention are as follows:

- Gaming apparatus having a known ordered series of indicia defined by the apparatus; indicia display means to display to a player of the gaming apparatus a selected one of the known ordered series of indicia; gamble control means operable by the player to select a class of indicia defined by either all the indicia of higher order or all the indicia of lower order in the known ordered series relative to the displayed selected one of the known ordered series; random selection means to select a new indicium of the known ordered series of indicia following said player's use of said gamble control means; compare means to determine if the randomly selected new indicium of the known ordered series of indicia is in the class of indicia selected by the player; and win means to produce a predetermined win response if the randomly selected new indicium of a known ordered series of indicia is in the class of indicia selected by the player.
 - Gaming apparatus as claimed in claim 1 wherein means are provided to display the fresh randomly selected indicium.
 after said gamble selection.
 - 3. Gaming apparatus as claimed in claim 1 or claim 2 wherein said display means is arranged to display the fresh randomly selected indicium as said selected one of the indicia for a further gamble selection by the player.
- 4. Gaming apparatus as claimed in any preceding claim wherein said win response is a standard value credit to the player.
- 5. Gaming apparatus as claimed in any preceding claim wherein said win means produces a predetermined lose response if the fresh randomly selected indicium is one of the indicia not

-12-

selected by the player.

- 6. Gaming apparatus as claimed in claim 5 wherein said lose response is a standard value debit to the player.
 - 7. Gaming apparatus as claimed in any preceding claim and including an intiate control operable by the



player to initiate operation of said random selection means.


- 8. Gaming apparatus as claimed in any preceding claim wherein said random selection means includes a window in the apparatus, a rotatable reel behind the window having the indicia marked about an annular or circumferential surface of the reel whereby one of the indicia markings on the reel can be viewed through the window as the selected indicium depending on the angular position of the reel, means to stop rotation of the reel at a randomly selected angular position to make said random selection of the indicium viewed through the window.
- 9. A fruit machine, as hereinbefore defined incorporating a gaming apparatus as claimed in any preceding claim and having means activating the gaming apparatus to make the apparatus available for play by the player of the fruit machine as a play feature following a normal play sequence of the fruit machine.

20

- 10. A fruit machine as claimed in claim 9 wherein said activating means activates the apparatus only following a winning play sequence of the fruit machine.
- 11. A fruit machine as claimed in claim 10 wherein said activating means is arranged to activate the 25 apparatus at random in response to a proportion of winning play sequences of the fruit machine.
 - 12. A fruit machine as claimed in any of claims 9 to 11, as dependent from claim 3, wherein said activating means maintains the apparatus activated for repeated fur-
- 30 ther gamble selections by the player until the fresh randomly selected indicium is one of the incidia not selected by the player.
- 13. A fruit machine substantially as hereinbefore *escribed with reference to and as illustrated in any 35 of the accompanying drawings.

DATEDULKES TWENTY NINTH day of SEPTEMBER, 1981 BALLY MANUFACTURING CORPORATION

patent attorneys for the Applicant SPRUSON & PERGUSON



This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:				
BLACK BORDERS				
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES				
☐ FADED TEXT OR DRAWING				
BLURRED OR ILLEGIBLE TEXT OR DRAWING				
☐ SKEWED/SLANTED IMAGES				
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS				
GRAY SCALE DOCUMENTS				
☐ LINES OR MARKS ON ORIGINAL DOCUMENT				
REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY				
OTHER:				

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.